higher education & training

Department:
Higher Education and Training
REPUBLIC OF SOUTH AFRICA

NATIONAL CERTIFICATE: MULTIDISCIPLINARY DRAWING OFFICE PRACTICE

STRUCTURAL STEEL DETAILING N5

(8090225)

23 November 2023 (X-paper)
09:00–13:00

REQUIREMENTS: **One sheet of A2 drawing paper, one sheet of A3 drawing paper and one sheet of A4 drawing paper**

Calculators may be used.
Candidates need drawing instruments or computers.

This question paper consists of 5 pages, 2 diagram sheets and 2 information sheets

072Q1E2323

Copyright reserved

DEPARTMENT OF HIGHER EDUCATION AND TRAINING
REPUBLIC OF SOUTH AFRICA

NATIONAL CERTIFICATE: MULTIDISCIPLINARY DRAWING OFFICE PRACTICE
STRUCTURAL STEEL DETAILING N5
TIME: 4 HOURS
MARKS: 100

INSTRUCTIONS AND INFORMATION

1. Answer all the questions.
2. Read all the questions carefully.
3. Number the answers according to the numbering system used in this question paper.
4. Each drawing question must be answered on a separate drawing sheet when using the computer.
5. Before any drawing work is done, a border must be retrieved from the symbols directory and displayed on the screen.
6. Plot the answers on ONE side of the drawing paper only.
7. All candidate information must be plotted in the title block.
8. Candidates are responsible, under suitable supervision, for the plotting of their own answers.
9. All the standard symbols (STRUCTURAL STEEL) may be obtained from the symbols directory.
10. Use your own discretion for numbers not given.
11. Computers may be used as drawing aids.
12. All drawing work must comply with the relevant SANS (SABS) recommended codes.
13. All abbreviations and symbols must comply with the latest National Building Regulations and ALL relevant SANS (SABS) codes.
14. Work neatly.

Copyright reserved

QUESTION 1: STEEL PROFILES

1.1 To scale 1:1, draw a fully labelled section through the following steel profile:

Rolled steel angle, 150 × 75 × 12

Neatly print the size and scale of the profile centrally beneath the drawing. (7)

1.2 Name THREE principal views in orthographic projection. (3)

[10]

QUESTION 2: BEAMS

FIGURE 1, DIAGRAM SHEET 1 (attached) shows a view of a steel structure.

Make fully detailed drawings (scale 1:10) of the beams marked B1 and B2 and supply enough information for the manufacturing of the beams in a workshop. AII plates are 10 mm thick and all bolts are M20.

Show the following information:

2.1 The column centres

2.2 Lengths and sizes of beams

2.3 Dimensions of the beams over end plates

2.4 Dimensions for the drilling of the bolt holes

2.5 View with dimensions of end plates

2.6 Item marks, number of beams required and diameter of bolt holes

2.7 Top of beams

Use your own discretion for information not given.

[25]

Copyright reserved

QUESTION 3: COLUMNS

Refer to FIGURE 1, DIAGRAM SHEET 1 (attached) and make fully detailed drawings (scale 1:10) of the columns marked C1 and C2. Supply enough information for the manufacturing of the columns in a workshop. All plates are 10 mm thick and all bolts are M20.

Show the following information:

3.1 Lengths and sizes of columns

3.2 Dimensions of the columns over cap and base plates

3.3 Dimensions for the drilling of the bolt holes

3.4 View with dimensions of cap and base plates

Use your own discretion for information not given.

[25]

QUESTION 4: LATTICE GIRDERS

FIGURE 2, DIAGRAM SHEET 2 (attached) shows a line diagram of a typical welded lattice girder.

To scale 1:5, draw typical details of the following:

4.1 Detail A (6)

4.2 Detail B (6)

4.3 Detail C (6)

Specifications:

- Top and bottom booms: rolled steel angle profiles, 120 × 120 × 10
- All internal members: rolled steel angle profiles, 90 × 90 × 8
- All gusset plates are 10 mm thick.
- Do NOT insert any dimensions.
- Use your own discretion for gusset plate sizes and other information not provided.

Print a suitable title and scale centrally below the details. (2)

[20]

Copyright reserved

QUESTION 5: TRUSSES

5.1 Refer to FIGURE 1, DIAGRAM SHEET 1 (attached) and draw to scale 1:20 a line diagram of the bolted steel roof truss. (6)

5.2 To scale 1:5, draw typical bolted details at A and B. (14)

Specifications:

- Top and bottom boom: 90 × 90 × 10 rolled steel angle profiles
- All internal members: 70 × 70 × 10 rolled steel angle profiles
- Gusset plates: 10 mm thick
- Us bolt hole centres of 100 mm and edge distances of 35 mm.
- All bolt holes are drilled on the centre lines of the angles and all bolts are M16.
- Insert suitable dimensions.

[20]

TOTAL: 100

Copyright reserved

DIAGRAM SHEET 1




FIGURE 1

B1 – UB 254 x 146 × 31 kg/m

B2 and B3 – UB 203 × 133 25 kg/m

C1, C2, C3 – UC 203 × 203 × 46 kg/m

C4 – UC 203 × 133 × 25 kg/m

End plates – 10 mm with 4 × M20 bolts

Base plates – 20 mm with 2 × M20 bolts

Copyright reserved

DIAGRAM SHEET 2





FIGURE 2

Copyright reserved

INFORMATION SHEET 1




Dimension c is to face of end plate or angle cleat.
r = 10mm minimum
Dimensions are in mm.

	Section	c	Notch			Section	c	Notch	
			l_1	h_1				l_1	h_1
I - Sections (parallel flange)	100 x 55 x 8	4	33	15	I - Sections (parallel flange)	533 x 210 x 82	4	33	15
	120 x 64 x 19	4	37	15		93	4	37	15
	140 x 73 x 13	4	42	20		101	4	42	20
	160 x 82 x 16	5	47	20		109	5	47	20
	180 x 91 x 19	5	51	20		122	5	51	20
	200 x 100 x 22	5	56	25		610 x 229 x 101	5	56	25
	203 x 133 x 25	5	74	20		113	5	74	20
	30	5	74	20		125	5	74	20
	254 x 146 x 31	5	81	20		140	5	81	20
	37	5	81	25	I - Sections (taper flange)	127 x 76 x 13	5	81	25
	43	6	81	25		152 x 89 x 17	6	81	25
	305 x 102 x 25	5	57	25		178 x 102 x 22	5	57	25
	29	5	57	20		203 x 102 x 25	5	57	20
	33	5	57	20		52	5	57	20
	41	5	91	25		254 x 152 x 59	5	91	25
	46	5	91	25		305 x 152 x 66	5	91	25
	54	6	91	25	Channels	100 x 50 x 11	6	91	25
	356 x 171 x 45	5	94	25		120 x 55 x 13	5	94	25
	51	5	94	25		140 x 60 x 16	5	94	25
	57	6	94	30		160x 65 x 19	6	94	30
	67	7	94	30		180 x 70 x 22	7	94	30
	104 x 140 x 39	5	78	25		200 x 75 x 25	5	78	25
	46	5	78	25		220 x 80 x 29	5	78	25
	54	6	97	25		240 x 85 x 32	6	97	25
	60	6	97	30		260 x 90 x 38	6	97	30
	67	6	97	30		280 x 95 x 42	6	97	30
	457 x 191 x 67	6	103	25		300 x 100 x 46	6	103	25
	75	7	103	30		76 x 38 x 7	7	103	30
	82	7	103	30		127 x 64 x 15	7	103	30
	90	7	103	30		152 x 75 x 18	7	103	30
	98	8	103	35		178 x 54 x 15	8	103	35
H - Sections	152 x 152 x 23	5	84	20		381 x 102 x 55	5	84	20
	30	5	84	20	H - Sections	254 x 254 x 107	5	84	20
	37	6	84	20		132	6	84	20
	203 x 203 x 45	6	111	25		167	6	111	25
	52	6	111	25		305 x 305 x 97	6	111	25
	60	7	111	30		118	7	111	30
	72	7	111	30		137	7	111	30
	86	8	111	35		158	8	111	35
	254 x 254 x 73	6	138	30		198	6	138	30
	89	7	138	35		240	7	138	35

Copyright reserved


INFORMATION SHEET 2

Recommended gauges and back marks for I- and H-sections



b (mm)	Gauge (mm)			Ø max. (mm)
	g_1	g_2	g_3	
64	32	120	60	12
73–82	40	140	75	12
89–91	50			12
102	54			16
133–146	70			20
152	90			20
165–191	90			24
203–254	140			24
305	140			24
368–406	140			24

Recommended gauges and back marks for angles



h or *b* (mm)	Back mark g_1 (mm)	Ø max. (mm)	*h* or *b* (mm)	Back mark (mm)				*h* or *b* (mm)
				g_1	g_2	g_3	g_4	
25	15	8	90	50	45	45		24
30	17	10	100	50				24
35	20		120	60				24
40	22		120					16
45	25		125	65				24

Copyright reserved